



MoonLite™ is a brand new patent-pending wireless lighting control product with LumenRadio's updated award winning ultra-reliable CRMX technology combined with Bluetooth connectivity and a built-in battery.

By being a wireless DMX transmitter and receiver, MoonLite™ is truly the Swiss army knife of the wireless DMX world!

## BUILT ON THE LATEST CRMX TIMOTWO TECHNOLOGY

MoonLite™ is built on LumenRadio's patented reliable CRMX technology and boosts new features such as:

- Bluetooth connectivity
- Control and configure your Moonlight through CRMX toolbox app
- Smarter disturbance detection technology, allowing for even more stable connectivity
- Significantly reduced RF footprint with dynamic transmissions


With built-in support for Bluetooth connectivity, MoonLite™ enables tablet and phone based lighting control softwares to connect directly without the need for extra hardware.

MoonLite™ is a state-of-the-art transceiver; thanks to its small size, built-in battery and dual XLR connectors it is ideal for use at clubs, small stage events, corporate events, in theaters and temporary events where wireless DMX connectivity is needed.

MoonLite™ has the same reliable functionalities as all LumenRadio's CRMX products, but is updated with even smarter disturbance detection technology, allowing for even more stable connectivity - and it comes in a much smaller package.

## FEATURES

- Built on the latest CRMX technology
- DMX transceiver (TX and RX)
- DC power
- Bluetooth connectivity
- Rechargeable battery included (10-12 hours in CRMX RX)
- Check battery status through app
- Color coded pairing indication
- Velcro fastening
- Firmware updates available over Bluetooth or XLR



What better way to control and configure your MoonLite™ than from the palm of your hand? Using our new CRMX Toolbox app you can quickly identify your Moonlite™, check battery status, conduct firmware updates, toggle between receiver and transmitter mode, change output power and much more. The new era of wireless DMX is finally here!

## TECHNICAL SPECIFICATIONS

### SUPPORTED PROTOCOLS

- USITT DMX512, DMX512(1990) & DMX512-A
- Bluetooth 5.0
- Compatible with all CRMX products

### RF CHARACTERISTICS


- Operational frequency range: 2402-2480 MHz
- Output power levels: 15mW, 40mW, 100mW

### CONNECTORS

- DMX: 2 XLR, 5-pin gold plated, female and male
- Antenna: Internal
- DC: USB Micro-B

### POWER

- Low voltage input: 5VDC



## CONTACT

### Sweden – Headquarters

LumenRadio AB  
Svangatan 2B  
416 68 Göteborg

+46 31 301 03 70  
sales@lumenradio.com

### Germany – Sales office

LumenRadio Deutschland GmbH  
Mergenthalerallee 10-12  
D-65760 Eschborn, Frankfurt

+49 619 658 655 590  
sales@lumenradio.com