

BACnet MS/TP THROUGH RELIABLE WIRELESS MESH

W-BACnet replaces the cabling with a reliable wireless mesh eliminating the time-consuming installation planning, cabling, daisy-chaining and trouble-shooting.

With W-BACnet, it is easy to retrofit connectivity to already installed devices, instantaneously converting individually siloed devices to a wireless network. The product enables flexibility, saving time and costs, including during installation and steady-state operation.

W-BACNET WALL MOUNT

Replace your BACnet MS/TP cable with a wireless connection between BACnet devices.

W-BACNET WALL MOUNT PRO

With the PRO version, up to four BACnet MS/TP devices can be connected to one W-BACnet PRO Node.




W-BACNET NODE

Can be hidden behind a wall.



W-BACNET DIN RAIL

A perfect fit for your BACnet MS/TP controller in a DIN rail cabinet.



INSTANT INSTALLATION

Installation is quick and easy. Connect your BACnet device to the W-BACnet node and then power up. The mesh network will form itself over a few minutes, avoiding time-consuming and un-aesthetical cabling.



UNIQUE RELIABILITY

By utilizing our Cognitive Coexistence technology in MiraMesh, each W-BACnet node possesses unparalleled reliability and resilience to interference.



MULTIPLE MS/TP DEVICES - PRO

With W-BACnet PRO you will be able to daisy chain up to four BACnet MS/TP devices behind one W-BACnet PRO unit.

FEATURES


- Out-of-the-box installation – power up and connect to your BACnet MS/TP device and you are up-and-running.
- Instant commissioning – 3 simple steps, commission the W-BACnet network in minutes.
- Mesh network – cover an entire building, utilizing the mesh network as your infrastructure.
- Range – 500 meters (line-of-sight) per hop in the mesh network.

- Cognitive Coexistence – LumenRadio's patented technology provides industrial-grade reliability and immunity to interference.
- Self-optimizing network – the mesh network will always find the best way to send messages through the network between devices.
- Modular configuration – no need for the same baud rate across all devices, W-BACnet supports individual settings.


SYSTEM OVERVIEW

A W-BACnet network consists of a single W-BACnet Gateway with up to 100 W-BACnet Nodes.

The W-BACnet PRO nodes can be connected to one to four Bacnet MS/TP devices over a BACnet MS/TP cable compared to a normal W-BACnet node that can connect to one MS/TP device over BACnet MS/TP cable.



GET IOT READY TODAY add your own uniqueness tomorrow



CONTACT

Headquarters

 **Sweden, Gothenburg**
LumenRadio AB
Johan Willins gata 6
416 64 Göteborg

+46 31 301 03 70
sales@lumenradio.com

Sales offices

 **Germany, Frankfurt**
+49 619 658 655 590
sales@lumenradio.com

 **US, Boston**
+1 617-901-9382
sales@lumenradio.com